

HTU-500

KEY FEATURES:

- Compact Size
- Powder coated cabinet
- Wall mountable
- Easy to use
- Ideal for everyday applications

PRODUCT DESCRIPTION

The HTU-500 ozone generator is an ideal economic solution for personal use applications such as hot tubs and other applications where less than 1 gram/hour of ozone is required. This unit can be run via suction or through the optional air pump.



AZCO INDUSTRIES LIMITED
ADVANCED OZONE SYSTEMS



SPECIFICATIONS

	HTU500 (E*)	POG	POG (E*)
General			
Voltage [VAC, 50/60Hz]	100-120 (200-240)	100-120	200-240
Power Consumption [W]	26		
Ambient Temperature [°C]	2 to 40		
Relative Humidity [%]	92		
Mass [Kg]	2.6 (3.4)	2.3	3.2
Dimensions [L x W x H][mm] <small>1 mm = .039 inches</small>	372 x 182 x 104	280 x 148 x 104	344 x 180 x 104
Installation	Refer to AZCO's installation manual for specific product		
Warranty (Refer to AZCO warranty sheet for more detail)	3 Year		
Ozone			
Generation Process	Pulse, Corona Discharge		
Process Gas [bar] <small>1 bar = 14.5 psi</small>	Dry air or oxygen, free of dust and oil. Maximum pressure ± 0.36 Bar		
Production On Oxygen [Refer to Graph for more detail]	~1 g/hr @ 1 l/min	~0.75 g/hr @ 1 l/min	~0.75 g/hr @ 1 l/min
Options			
Internal Air Pump	O	N/A	N/A
Adjustable Output	S	N/A	N/A
Interlock	O	O	O
Flow Meter	N/A	N/A	N/A
Oxygen Ready	S	S	S
Flow Switch	N/A	N/A	N/A
Built-in Air Dryer	N/A	N/A	N/A
Safety			



E*: European Version, N/A: Not Applicable, O: Optional, S: Standard

