

# VMUS-2

## KEY FEATURES:

- Produces up to ~5.0g/hr.
- Wall mountable
- Easy to install and operate
- Compact form factor
- Powder coated Al. cabinet

## PRODUCT DESCRIPTION

The VMUS-2 is a wall mountable Ozone generator which produces up to 5.0g/hr of ozone @ 6 l/min of oxygen. Like all of our ozone generator, this generator utilizes our silent pulse injection corona discharge technology. This unit is typically used in small water bottling plants, self contained site remediation systems, and air systems for small commercial buildings.



AZCO INDUSTRIES LIMITED  
ADVANCED OZONE SYSTEMS



# SPECIFICATIONS

	VMUS-2 (E*)	VMUS-4 (E*)	SNOA-4 (E*)
<b>General</b>			
Voltage [ VAC, 50/60Hz]	100-120 (200-240)		
Power Consumption [W]	60	100	180
Ambient Temperature [°C]	2 to 28		
Relative Humidity [%]	10-92 (non-condensing)		
Mass [Kg]	4.5 (5.6)	5.2 (7.1)	8.6 (9.9)
Dimensions [L x W x H] [mm] <small>1 mm = .039 inches</small>	430 x 260 x 112	435 x 260 x 135	514 x 305 x 196
Installation	Refer to AZCO's installation manual for specific product		
Warranty [Refer to AZCO warranty sheet]	3 Year		
<b>Ozone</b>			
Generation Process	Pulse, Corona Discharge		
Process Gas [bar] <small>1 bar = 14.5 psi</small>	Dry air or oxygen, free of dust and oil. Maximum pressure ± 0.36		
Production on Oxygen [Refer to Graph for more detail]	~ 5.0 g/hr @ 6 l/min	~6.5 g/hr @ 6 l/min	~4.0 g/hr @ 6 l/min on dry air
<b>Options</b>			
Internal Air Pump	O	O	O
Adjustable Output	O	O	O
Interlock	O	O	O
Flow Meter	O	S	S
Oxygen Ready	S	S	O
Vacuum Switch	O	O	S
Built-in Air Dryer	N/A	N/A	S
<b>Safety</b>			



E\*: European Version, N/A: Not Applicable, O: Optional, S: Standard

